

10 Programmable Data Management Keys

Ten user-definable data management keys let you collect and/or display data as employees punch. Common data collection uses include department transfers, tips collected, job codes, or pay codes. The keys can also be defined to allow employees to review punches or find out about their schedules, vacation time accumulated, hours worked, and other programmed information. To reduce keystrokes, the keys can also be set to automatically enter data such as a frequently used department number or in/out status.

Other data management key features include

- Employee messaging
- Review of employee information fields
- Validation tables to ensure proper data entry
- Restrict employee access to specific data management keys
- User defined prompts- Multi-level input sequence definable per key
- Decision menus to minimize keystrokes

Schedules by Employee

Employee schedules may be downloaded to the HandPunch 4000 to restrict the times that an employee can punch. This can reduce unauthorized overtime as well as early "in" punches. A separate schedule can be defined for each employee providing the ultimate in flexibility.

Built-in Bar Code Reader

Some installations require the use of a badge. For these situations, the HandPunch 4000 includes an integrated bar code reader that can be used for ID number entry. The swipe-type reader supports the most popular bar code formats and allows for infrared badges.

Communications and Networking

Whether your needs are to network two terminals or thousands, the HandPunch 4000 can be configured to meet your needs. Standard RS-485 communications makes networking terminals easy and reliable. Options include an Ethernet Communications Modules and a high speed internal modem for remote sites. Each unit also provides RS-232 serial printer support.

Edit-at-the-Clock Functions

The HandPunch 4000 allows supervisors to override user restrictions and to input such items as missed punches, planned vacations, and sick time at the terminal. The password-protected mode provides greater supervisor flexibility by lessening the need for computer edits. Audit trails documenting the use of these functions are generated to ensure security.

Bell Schedules

The bell schedule lets you program the day, time, and duration of a series of bells. The bells can be programmed to signal the beginning or end of a shift, lunch, or break.

Door Control

The HandPunch 4000 provides the capability to unlock and monitor a door. An employee's individual schedule may be used to restrict access.

Antimicrobial Protection

A BioCote® antimicrobial agent containing silver is applied to the platen of the HandPunch during its manufacturing process. The BioCote® silver-based additive remains active for the life of the HandPunch reader. This high-tech agent provides a durable and safe finish that makes the platen's surface cleaner and more hygienic.

Hand Outline

The HandPunch comes standard with a blue hand outline printed on the platen. This hand outline will help new users place their hand accurately on the platen when using the terminal and decrease initial enrollment time.

SPECIFICATIONS

Part Number:	HP-4000
Size:	8.85 in (22.3 cm) wide 11.65 in (29.6 cm) high 8.55 in (21.7 cm) deep
Weight:	6 lbs (2.7 kg)
Power:	12 to 24 VDC or 12 to 24 VAC 50-60 H7 watts
Environment:	Operating: 32°F to 113°F (0°C to 45°C) Relative Humidity: 20% to 80% NC Non-operating (storage): 14°F to 140°F (-10°C to 60°C) Relative Humidity: 5% to 85% NC
Verification Time:	Less than one second
Memory Retention:	Up to 5 years via the standard internal lithium battery.
Transaction Storage:	7680 transactions
ID Number Length:	1 to 10 digits from keypad or card
User Capacity:	530 users expandable to 3,498 users
Template Size:	9 bytes
Communications:	RS-485 (4 and 2 wire) RS-232 Serial Printer Support or network communications
Baud Rate:	300 to 28.8 Kbps
Card Reader Input:	Proximity, Wiegand, Magnetic Stripe, Bar Code (5 VDC provided by HandReader)
Card Reader Output:	Wiegand, Magnetic Stripe, Bar Code
Data Management Keys:	10 keys, user definable
Supports:	Validation tables Employee information fields, 24 max Multi-level prompting Key restriction by employee Decision Menus Punch Review
Employee Messaging:	32 characters per message per employee
Employee Name:	16 characters
Employee Schedule:	Schedules definable for each employee
Internal Barcode Reader:	Code 39 Interleaved 2 of 5
Door Controls:	Door Lock Output (Sinks 0-24VDC, 100mA max.) Door Switch Monitoring Bell Ring Output (Sinks 0-24VDC, 100mA max.)
Options:	BB-200 Operational Battery Backup DC-102 Data Converter (RS-232 to RS-485) EM-805 Memory Expansion - 3,498 users EN-200 Ethernet Communications Module MD-500 Internal 14.4 Baud Dial-up Modem WAR-EXT 1 year extended warranty



HandPunch® is a registered trademark of Schlage. Specifications subject to change. Please check with your system vendor for details.